

PITBULL 2300B

Portable Box Screener "Quick Spec" Sheet

- Honda GX660RTX air cooled 2-cylinder gasoline industrial power plant rated at 21.5 HP
- 6 gallon poly fuel tank
- Honda optimized air cleaner system
- Electric start featuring Honda control panel with throttle control and low oil warning indicator
- Machine controls and engine control panel conveniently located together for easy operator access
- Engine, oil tank, fuel tank, and control compartment fully enclosed and lockable
- Curb weight in standard pintle hook configuration 7,300 Lbs.
- Tongue weight of 2,800 Lbs.
- 6,000 Lb. Dexter straight axle with electric brakes and safety breakaway controller
- Screen plant hydraulically adjusts from transport to operating position
- Positive mechanical axle locks for transport position
- 15" steel wheel 6 stud mount
- ST225/75R15 radial tires. Load range E, 8-ply rating
- Standard pintle hitch
- Standard hydraulic axle lift and park jack
- Hydraulic system over heat shut down protection
- 15 gallon hydraulic reservoir with spin-on filter and oil cooler
- Single stage gear pump providing 12 GPM at rated engine speed
- 3-section hydraulic valve with system relief
- Hydraulic direct drive shaker table featuring reverse rotation standard
- Two tier shaker table with loading apron and quick change screen panel tensioning system
- Fully welded and reinforced tubular steel frame with abrasion resistant inner bucket plate
- Screen panels fully interchangeable with all 2300 family of screening plants (both tiers)
- Common screen sizes available from 1/8" to 4" openings. Special application screen panels available

Available options. (Factory order or field installable)

Sorting chute for either or both deck levels

Spare tire and wheel

Customer/Dealer requests welcome